

Door Open / Close Sensor

74DOS - Door Sensor for SCW Shield



Features

- **Detects Door Status**
- **60 second delay**
- **6 year battery life**
- **1-inch magnet gap**
- **Double Sided Tape Mounting**
- **Discretely sized Nearly half the size of competitors**
- **5 Year Warranty**

Specifications

General	
Mounting	3M VHB Double Sided Tape (included)
Action (with professional monitoring)	60 seconds to disarm on entry - if triggered central station calls to verify. Without verification police are dispatched.
Warranty	5 Years
Certifications	UL634, ULC634, ETL, FCC, IC, EN50131-2-6, EN 60950-1, EN 300 220, EN 301 489, CE Security Grade 1, CE Environmental Class 2, RCM
Communication	
Frequency	433.92MHz
Magnet Range	Up to a 1-inch magnet gap
Range	1500FT Maximum with SCW Shield Hub
Compatibility	SCW Shield Hub
Physical & Power	
Battery	CR1632
Battery Life	6 year average
Operating Temperature	32 to 120 °F - 85% non condensing humidity
Dimensions	1.80 x 0.77 x 0.39 inches
Weight with battery	.5 ounces (15 grams)



For More Information Contact SCW

Toll Free: 1.866.414.2553 • Fax 1.866.337.9542 • Email sales@security-camera-warehouse.com

www.security-camera-warehouse.com